

## Precise digital measuring device Termio-2

High class precise temperature data logger which can be used in many different industries like Pharmacy, Laboratory, Transport and Gastronomy. The device is powered from battery. Comes with different types of probes which can be picked by the customer. All types of probes are shown on next page.

Technical data		
Temperature range	-100 °C to 300 °C	
Sensor Type	platinum PT-1000	
Resolution	0.01°C	
Accuracy	±0.07 °C(-10°C to 100°C)	
Sample rating interval	1 measurement per 30 seconds	
Record frequency	From 1 minute	
Dimensions	45 mm × 100 mm × 19 mm	
Protection	IP65-electronics	
Power	1x lithium battery 3.6V (1 / 2AA) included	
Case material	ABS	
Memory	32000 readings	
Sensor's Cover material	acid-resistant steel SS 321	
Producer Features:	Termoprodukt	

- Minimum and Maximum temperature
- Hold function
- Light weight (85g)
- Battery life approximately 8760 hours
- Compact shape and ergonomic design
- Simple to set up and use
- Start/Stop recording done by button, computer or from time/clock
- Alarm indication arrow on the display and blinking diode



Every device is calibrated in termoprodukt laboratory

## Temperature probes for Termio-2 data logger

List of probes in standard configuration. We offer more probes with different shape, diameters and ranges. If u want to check the probes offer visit our site

		Probe model	Technical data
50.00		ST-05-S	Resistance thermometer probe PT1000 Diameter: Ø4mm, Lead length: 1m (standard), Class A, Temperature range from -50°C to 270°C. Max lead temperature 180°C.
50.00		ST-05-FEP	Resistance thermometer probe PT1000 Diameter: Ø4mm, Lead length: 1m (standard), Class A, Temperature range from -100°C to 270°C. Max lead temperature 205°C.
50.00	ა ∪ 	ST-05-PFA	Resistance thermometer probe PT1000 Diameter: Ø3.3mm, Lead length: 1m (standard), Class A, Temperature range from - 100°C to 270°C. Max lead temperature 260°C.
100.00	80.00	ST-11	Resistance thermometer probe PT1000 Diameter: Ø3.1mm, Lead length: 1m (standard), Class A, Temperature range from - 100°C to 270°C.

We are able to make probes with different lead length, probe length, probe diameter and sensors like PT100/PT500 depending on your needs.

Contact us at: bok@termoprodukt.com.pl

